







## Novair Ultra Heat Series

-25°C

Size		9,000 BTU	12,000 BTU	18,000 BTU	24,000 BTU
Model Number		LEA09SZ25SK-O	LEA12SZ25SK-O	LEA18SZ25SK-O	LEA24SZ25SK-O
Power Supply		208/230V 1Ph 60Hz	208/230V 1Ph 60 Hz	208/230V 1Ph 60 Hz	208/230V 1Ph 60 Hz
Rated Cooling Capacity		2500-11900	3600-13300	5980-19500	9200-25000
Rated Heating Capacity		3400-13000	4500-13500	6620-21200	10350-26410
<b>Performance</b>					
SEER/EER		24/14.7	22.2/13	24/13.5	21/13
HSPF/COP		12.7/3.66	10.8/3.4	11.6/3.74	10/3.15
<b>Indoor Unit</b>					
Airflow	cfm	291/194/152	291/194/152	530/458/382	601/458/382
Sound Pressure Level	db(a)	40/34/23.5	42/36/25	45.5/41/24.5	48/40/28
Unit Dimensions	in	31.57x7.87 x11.61	31.57x7.87 x11.61	42.6x9.21 x13.27	42.64x9.61 x13.27
Net/Gross Weight	lbs	18.74/24.25	18.96/24.25	29.54/37.48	29.98/38.14
<b>Outdoor Unit</b>					
Compressor Type		Rotary	Rotary	Rotary	Dual Rotary
Sound Pressure Level	db(a)	53	53.5	58	60
Unit Dimensions	in	30.12x11.93 x21.85	30.12x11.93 x21.85	34.04x13.46 x26.50	37.24x16.14 x31.89
Net/Gross Weight	lbs	63.71/69.00	63.71/69.00	95.02/101.85	124.78/134.92
Refrigerant		R410A	R410A	R410A	R410A
Line Set Size		1/4" - 3/8"	1/4" - 1/2"	1/4" - 1/2"	3/8" - 5/8"
Max Line Run	ft	82	82	98	164
Max Elevation	ft	33	33	66	82
Minimum Ampacity	A	13	13	17	22
MCA	A	15	15	25	30
Energy Star					
Wire Size	16 awg*4 stranded, unshielded				



novairplus.com